

# **STALL FLOORING**

For cattle farming Fattori srl manufactures grids according to the requirements of the European standard EN 12737:2007 which imposes precise characteristics:

- Rck 40 concrete
- guaranteed durability in XC3 classified environments
- high quality B450C steel calculated to ensure the required performance
- slots with a width of 3.20 cm and rounded to limit the possibility of injury to the feet
- production lots that allow the traceability of the raw materials used and provide further guarantees for the purchaser

The production process is monitored at every stage, starting from the incoming raw materials, and in every single process until the loading of the finished product.

It is a cutting edge product at a European level.









# **TECHNICAL SPECIFICATIONS**

# **PLAN**



# **LONGITUDINAL SECTION PLAN VIEW**



#### TECHNICAL CHARACTERISTICS OF THE ELEMENT

#### VARIABLE LIVE LOAD:

1500 kg/mq in addition to its own weight

#### CONCRETE:

R'ck formwork ≥ 20 N/mmq

R'ck in 28 day≥ 40 N/mmg

#### STEEL B450C checked:

fyk ≥ 450 N/mmq

ftk ≥ 540 N/mmq

## WELDMESH:

Steel B450A

### EXPOSURE CLASS

bar cover

2,5cm ≥ 2 cm ≥ Ø max bar free interspace

REI 30

### **TOLLERANCES**

± 1,0 cm lenght ± 0,5 cm height widht ± 1,0 cm mild reinforcement ± 1,0 cm

ITEM CODE	A cm	B cm	C cm	D cm	E cm	Flow Kg/mq	Weight Kg/cad	Empty mq	Full mq	Ratio Empty/ full
GBT4105030	410	50	30	11,5	4,0	1200	742	0,364	1,686	21%
GBT4205030	420	50	30	11,5	4,0	1200	760	0,344	1,756	20%
GBT4505030	450	50	30	11,5	4,0	1200	815	0,407	1,843	22%
GBT5005030	500	50	30	11,5	4,0	1200	905	0,455	2,045	22%